product datasheet collated coarse thread drywall screw (phosphate)



www.evolutionfasteners.co.uk













Fine thread screws have diminished holding power as wood dries.

Evolution coarse thread drywall screws have fewer threads so require fewer revolutions meaning faster installation. They also have deeper threads for superior holding power.



Fibres are pulled up during installation. As wood dries the natural tendency of wood fibres is to spring back to their original position. Wood pulls the screws inwards, eliminating 'head pops'.

Evolution Fasteners (UK) Ltd Unit 2A & 2B Clyde Gateway Trade Park Dalmarnock Road Rutherglen Glasgow G73 1AE

Tel: +44 (0)141 647 7100 Fax: +44 (0)141 647 5100 technical@evolutionfasteners.co.uk

Designed for:	Fixing plasterboard to timber studs.
Head Style:	Bugle
Drive Bit:	Phillips 2
Drill Point:	Super sharp point
Thread Form:	Single thread, fine
Coating:	Black phosphate
Shank Material:	Carbon steel
Material Grade:	AISI C1022
Effective Thread Length:	Fully threaded
Recommended Drill Speed:	2,000 - 3,000 RPM
Steel Thickness:	0.5mm - 1.0mm

IMPORTANT APPLICATION ADVICE

On rare occasions black phosphate screw coatings can react with some render types, which can damage the coating resulting in corrosion and staining.

To reduce the risk of this happening Evolution recommends sealing the drywall screw heads with a PVA bonding solution before render is applied.

Collated Coarse Phosph	ollated Coarse Phosphate Drywall Range				
Product Code	Size	Box Qty	Carton Qty	Fixture Thickness	
CDWCP25	3.5mm x 25mm	1,000	10,000	8mm	
CDWCP32	3.5mm x 32mm	1,000	10,000	12mm	
CDWCP35	3.5mm x 35mm	1,000	10,000	15mm	
CDWCP38	3.5mm x 38mm	1,000	10,000	18mm	
CDWCP42	3.5mm x 42mm	1,000	10,000	20mm	
CDWCP45	3.5mm x 45mm	1,000	10,000	22mm	
CDWCP50	3.5mm x 50mm	1,000	10,000	25mm	
CDWCP55	3.5mm x 55mm	1,000	10,000	30mm	
CDWCP65	3.9mm x 65mm	500	5,000	45mm	
CDWCP75	3.9mm x 75mm	500	5,000	55mm	

Ultimate Mechanical Performance					
Diameter	Tensile Strength	Shear Strength	Torque		
3.5mm	1.4kN	0.8kN	2.7Nm		
4.2mm	1.6kN	0.9kN	2.9Nm		

Hardness Ratings (Vickers)			
Diameter	Surface Hardness		
3.5mm	550HV		
4.2mm	550HV		

Ask for Evolution



Tek Screws



Masonry Screws





Anchors Clips & Brackets