

product datasheet

stainless steel drywall screw



www.evolutionfasteners.co.uk



Designed for:	Fixing plasterboard to drywall track and timber in humid atmospheres
Head Style:	Countersunk
Drive Bit:	Phillips 2
Shank Material:	Stainless steel
Threadform:	Hi-Lo
Drill Point:	Tek 2
Material Grade:	AISI 410 stainless steel
Effective Thread Length:	Fully threaded

Evolution Fasteners (UK) Ltd
 Unit 2A & 2B
 Clyde Gateway Trade Park
 Dalmarock Road
 Rutherglen
 Glasgow
 G73 1AE
 Tel: +44 (0)141 647 7100
 Fax: +44 (0)141 647 5100
 technical@evolutionfasteners.co.uk

Stainless Steel Drywall Screw						
Product Code	Size	Box Qty	Carton Qty	Fixture Thickness	Steel Thickness	Drill Speed
SSDW4242	4.8 x 42mm	200	4,800	30mm	0.8mm - 2.5mm	3,000 - 4,000 RPM

Ultimate Pull Out Values							
Steel Thickness						Timber Embedment (C16 Grade)	
0.8mm	0.9mm	1.2mm	1.5mm	2.0mm	2.5mm	15mm	27mm
0.7kN	0.8kN	1.2kN	1.4kN	1.9kN	2.4kN	0.8kN	1.5kN

Ultimate Mechanical Performance		
Diameter	Tensile Strength	Shear Strength
4.2mm	7.0kN	4.8kN

Ask for Evolution



Drywall Screws



Tek Screws



Collated Screws



Masonry Screws



Anchors



Clips & Brackets