

## NEW Improved Paslode Impulse IM50 F18 Fine Finish Gas Brad Nailer



### The NEW Improved IM50 F18

The IM50 brad nailer is ideal for fine finish applications and boasts a small, light shell, excellent depth of drive and easy jam clearance. Now supplied with two batteries for the same great price.

### Product Advantages

- Powerful motor - Drives 16 - 50mm brads
- Compact design - Allows for easy access
- Sequential operation - 2 - 3 brads per second for limited periods, normal firing rate is up to 1,000 brads per hour
- Reversible belt hook - Easy access when not in use
- Tool free depth of drive adjustment - Provides precise control of nail depth
- With 2 batteries as standard - 4,000 brads per charge
- Nail lock-out feature - Preventing blank firing and minimising wood damage
- No-mar contact with sight lines - For accurate placement and reduced damage to wood
- Mini fuel cell - Drives up to 1,000 brads per cell
- 18 gauge for finer finish work
- Quick clear nose cover - Easy access in the unlikely event of a jam
- Side load magazine - Easy nail loading, holding 2 strips of brads (100 brads)
- Comfortable handle and soft trigger - Providing increased user comfort

### Kit Contains

Paslode Impulse IM50 F18 Fine Finish Brad Nailer, high impact lightweight carry case, 2 x batteries as standard, battery charger, cleaning solution, Impulse lubricant, safety glasses to EN166:F, allen key and instruction manual

### Substrates

- Wood
- MDF and similar substrates

### Applications

- Architrave
- Skirting board
- Beading
- Panelling
- Cabinet work
- Furniture trim
- Glazing bead
- Exhibition and display work
- Shop fitting and remodelling
- Secret nailing

### Tool Specification

|                    |                                 |
|--------------------|---------------------------------|
| Weight             | 2.1kg                           |
| Dimensions         | 292 x 272 x 90mm                |
| Brad range         | 32mm to 50mm                    |
| Cycle rate         | 2 - 3 brads per second          |
| Maximum cycle rate | 500 per hour 3,000 per day      |
| Magazine capacity  | 100 brads                       |
| Fuel cell life     | Approx 1,000 brads              |
| Battery            | Approx 4,000 fixings per charge |
| Charger 230 volt   | Maximum charge time of 2 hours  |

### Fastener Specification

|                                 |                      |
|---------------------------------|----------------------|
| Coatings / Materials / Finishes | Galvanised           |
| Brad Gauge                      | F18 Wire size 1.22mm |
| Point Types                     | Diamond Point        |
| Head Types                      | Lost Head            |
| Collation Types                 | Glued                |



## NEW Improved Paslode Impulse IM50 F18 Fine Finish Gas Brad Nailer

| Eurocode | Description                 | Box Qty |
|----------|-----------------------------|---------|
| 013331   | IM50 F18 Fine Finish Nailer | 1       |

### Product Range - Brad and Fuel Packs for IM50 F18 and IM200 / F18

| Eurocode | Gauge | Length | Brad Finish | Fuel Cells | Box Qty |
|----------|-------|--------|-------------|------------|---------|
| 395192   | F18   | 16mm   | Galv        | 2          | 2,000   |
| 395193   | F18   | 25mm   | Galv        | 2          | 2,000   |
| 395194   | F18   | 32mm   | Galv        | 2          | 2,000   |
| 395195*  | F18   | 38mm   | Galv        | 2          | 2,000   |
| 395196   | F18   | 50mm   | Galv        | 2          | 2,000   |

\* Order to order, minimum order quantities apply.