

## NEW Paslode IM90i Fuel Injection System Nailer



### The next generation in cordless nailing technology

The NEW Paslode IM90i is the first cordless nailer powered by an intelligent electronic fuel injection system offering unrivalled cold weather performance. Having been tested to work in temperatures as low as -15°C the IM90i delivers consistent nailing time after time.


### Product Advantages

- Temperature performance - intelligent fuel injection system delivers unrivalled cold weather performance with a working threshold of -15°C to +49°C
- More power - new improved nailing system produces 105 joules of power, providing users with the ability to drive 90mm Ring Shank Nails into C24 structural timber
- RounDrive® Nails - a unique off-centre design and are the only full-head 34° nails available in paper strip collation
- Removable magazine - makes light work of clearing jams and debris from the tool
- Long magazine - saves time and effort during high volume nailing by using the double length magazine accessory, with 2 strip capacity
- Fuel cell loading - the patented locking system means the fuel cell self-locates into the lock position, making loading a simple operation
- On / Off battery - new easy click on / off settings enables the tool to be left in safe mode, without needing to remove the battery
- Depth Adjuster - the tool-free depth adjuster with its unique locking system means consistent nail embedment every time
- Indicator lights - LED lights indicate; battery charge - green for positive charge, red for low charge; tool cleaning - flashes orange after 30,000 shots to indicate it is time to clean the tool
- Soft grip handle - Rubber grip increases comfort over long working periods by improving tool handling

### Tool Specification

Weight	3.7kg
Dimensions	380 x 324 x 113mm
Power	105 J
Nail range	50mm to 90mm
Cycle rate	2 - 3 nails per second
Maximum cycle rate	1,000 nails per hour, 4,000 per day
Magazine capacity	Standard - 1 strip / 37 nails Long - 2 strips / 74 nails
Fuel cell capacity	1,250 shots at -5°C
Battery NiMH 1.5 Ah 6V	4,000 shots at -5°C 2 hours maximum charge

### Fastener Specification

Coatings / Materials / Finishes	Bright ● Galv Plus® ●	Hot Dipped Plus ● Stainless Steel ●
Shank Types	Ring Shank 2.8 / 3.1mm Uni Lock 3.1mm Smooth Shank 3.1mm	
Point Types	Diamond Point	
Head Types	Full Round Head	
Collation Types	RounDrive® Nails: A unique off-centre design. Only full-head 34° nails available in paper strip collation.	

### Kit Contains

Paslode IM90i Nailer, high impact lightweight carry case, 2 x batteries, battery charger, intensive cleaning solution, Paslode lubricating oil, safety glasses to EN166:F, allen key, instruction manual and tool schematics & part list

### Substrates

- Wood

### Applications

- Timber frame
- Floor boarding
- Roof battening
- Decking
- Flat roofing
- Chipboard
- Shuttering
- Cladding
- Joists
- Noggins
- Soffits
- Refurbishment
- Panelling
- Fencing
- Packaging



## NEW Paslode IM90i Fuel Injection System Nailer

Eurocode	Description	Box Qty
010333	IM90i Nailer	1

### Product Range: Nail Fuel Packs - Bright

Eurocode	Product Description	Box Qty
142005	2.8 X 51mm RING BR	3,750
142011	2.8 X 63mm RING BR	3,750
142029	3.1 X 75mm RING BR	2,500
142035	3.1 X 90mm SMOOTH BR	2,500
142036	3.1 X 90mm RING BR*	2,500

### Product Range: Nail Fuel Packs - Galv Plus®

Eurocode	Product Description	Box Qty
142007	2.8 X 51mm RING GP	3,750
142009	2.8 X 57mm RING GP	3,750
142013	2.8 X 63mm RING GP	3,750
142024	3.1 X 63mm RING GP	2,500
142030	3.1 X 75mm RING GP	2,500
142037	3.1 X 90mm SMOOTH GP	2,500
142038	3.1 X 90mm RING GP*	2,500

### Product Range: Nail Fuel Packs - Hot Dipped Galv

Eurocode	Product Description	Box Qty
142014	2.8 X 63mm RING HDGV	3,750
142025	3.1 X 63mm RING HDGV	2,500
142031	3.1 X 75mm RING HDGV	2,500
142039	3.1 X 90mm SMOOTH HDGV	2,500
142040	3.1 X 90mm RING HDGV*	2,500

### Product Range: Handy Packs - Stainless Steel

Eurocode	Product Description	Box Qty
142045	2.8 X 51mm RING SS	1,250
142047	2.8 X 63mm RING SS	1,250
142050	3.1 X 80mm RING SS	1,250

\*C24 structural grade timber